



4200



15 Hp Diesel Engine

Maximize your production (open-blow) with our #4200 **all-fiber** (airlock) machine, featuring a large 14 inch (35.5cm.) diameter by 14 inch (35.5cm.) long airlock. Designed for low maintenance and high production, the #4200 provides large hopper capacity and easy loading, while offering simple rugged performance. The #4200 is intended to function as a truck mount machine for the **professional contractor** or for use in manufactured housing.

MATERIAL PRODUCTION RATE

MATERIAL	lbs/hr (kg/hr)
CELLULOSE	4200 (1905)
FIBERGLASS	1800 (816)



lbs/hr (kg/hr) rating with 150ft. (45.8m.) of 4" (10.2cm.) hose at 16ft. (4.9m.) elevation
Product density and variable blowing conditions will affect production rate.

STANDARD FEATURES AND BENEFITS

WEIGHT

1700 lbs. (771 kg.)

DIMENSIONS

42"W x 72"D x 82"H
(106cm. W x 183cm. D x 208cm. H)

HOPPER CAPACITY

49 cu. ft. (1.38 m³)

AIRLOCK

14" x 14" diameter (35.5cm. x 35.5cm. diameter)
SlideOut Removable Airlock
4" (10cm.) outlet for blowing hose

BLOWERS/SIZES

Positive Displacement Blower provides
170 CFM @ 5psi

OPTIONAL EQUIPMENT

Wireless remote

Mechanical

- Modular component design for easy troubleshooting and maintenance
- Safety guards provide operator safety
- 49 cu. ft. (1.38 m³) hopper provides large capacity
- Three (3) agitators that enhance the condition of fibers
- Removable all steel airlock allows quick access to airlock for replacing seals
- Shredder assembly increases production and material conditioning
- Gear reducer (3070 in./lb. torque) provides durable direct drive transmission for the toughest blowing materials
- Extra heavy, nickel plated #50 chain with hardened steel sprockets provides a rugged, corrosion/abrasion resistant drive system
- Check valve protection and pressure relief on the positive displacement blower
- 15 Hp diesel engine

Electrical

- Operator safety/Hazard response features: pre-alarm buzzer, main disconnect/power interruption shutdown, emergency kill switch, manual override at the machine, 150 ft. (46m.) of remote control cord